

View Online at https://aerobasegroup.com/nsn/5970-00-059-5181

Reliability Indicator: Not established Tempurature Rating: -55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant and solvent resistant and water resistant Main Body Inside Diameter: 0.520 inches as supplied First Branch Inside Diameter: 0.260 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
 -55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant and solvent resistant and water resistant Main Body Inside Diameter: 0.520 inches as supplied First Branch Inside Diameter: 0.260 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
Environmental Protection: Flame resistant and mildew resistant and solvent resistant and water resistant Main Body Inside Diameter: 0.520 inches as supplied First Branch Inside Diameter: 0.260 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.920 inches after unrestricted recovery
Flame resistant and mildew resistant and solvent resistant and water resistantMain Body Inside Diameter:0.520 inches as suppliedFirst Branch Inside Diameter:0.260 inches as suppliedDistance From Intersecting Centerline Of Main Body To End Of First Branch:0.920 inches after unrestricted recoveryMain Body Wall Thickness:0.060 inches after unrestricted recoveryFirst Branch Wall Thickness:0.040 inches after unrestricted recoveryDistance From Edge Of Main Body To Intersecting Centerlines:0.900 inches after unrestricted recovery
Main Body Inside Diameter:0.520 inches as suppliedFirst Branch Inside Diameter:0.260 inches as suppliedDistance From Intersecting Centerline Of Main Body To End Of First Branch:0.920 inches after unrestricted recoveryMain Body Wall Thickness:0.060 inches after unrestricted recoveryFirst Branch Wall Thickness:0.040 inches after unrestricted recoveryDistance From Edge Of Main Body To Intersecting Centerlines:0.900 inches after unrestricted recovery
0.520 inches as supplied First Branch Inside Diameter: 0.260 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
First Branch Inside Diameter: 0.260 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
0.260 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
Distance From Intersecting Centerline Of Main Body To End Of First Branch: 0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
0.920 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
Main Body Wall Thickness: 0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
0.060 inches after unrestricted recovery First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
First Branch Wall Thickness: 0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
0.040 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines: 0.900 inches after unrestricted recovery
0.900 inches after unrestricted recovery
-
Main Bodylength:
1.940 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
45.0 after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Rubber, neoprene, rt-501, taychem corporation or rubber, neoprene, mpn-195 electronized chemicals corp
Material:
Rubber, neoprene, rt-501, taychem corporation or rubber, neoprene, mpn-195 electronized chemicals corp
Style Designator:
Transition-45 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5970-00-059-5181

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

