# NSN 5970-00-099-5886

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-099-5886

# **Reliability Indicator:**

Not established

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

## Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

# Small End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

#### Distance From Intersecting Centerlines To Edge Of Small End:

Any acceptable as supplied

## Distance From Centerline Of Small End To Edge Of Large End:

Any acceptable as supplied

## Main Body Small End Inside Diameter:

1.750 inches as supplied

## Main Body Large End Inside Diameter:

1.750 inches as supplied

## Distance From Top Of Shoulder To Small End Of Main Body:

Any acceptable as supplied

# Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

# Min. Tensile Strength (psi):

1200 pounds per square inch

# Special Features:

Includes molding ports

# Flexibility:

Flexible

# Height:

Any acceptable as supplied

#### Color:

Black

### Material:

Plastic, polyolefin, rt-1304-08795

# Material:

Plastic, polyolefin, rt-1304-08795

## **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-00-099-5886

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500