

View Online at <https://aerobasegroup.com/nsn/5970-00-104-2650>

Dielectric Withstanding Voltage In Volts:

200.0

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 225.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant

Distance From Centerline Of Main Body To End Of First Branch:

0.760 inches after unrestricted recovery

Main Body Inside Diameter:

0.520 inches as supplied

First Branch Inside Diameter:

0.260 inches as supplied

Main Body Wall Thickness:

0.040 inches after unrestricted recovery

First Branch Wall Thickness:

0.040 inches after unrestricted recovery

Main Bodylength:

2.200 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Breakout is 1.300 in. From left end; 0.150 in. Maximum right end diameter after unrestricted recovery

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Transition-t

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500