## NSN 5970-00-110-8430

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-110-8430

## **Reliability Indicator:**

Not established

#### **Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

## Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

#### Main Bodylength:

3.200 inches after unrestricted recovery

#### Main Body Small End Inside Diameter:

0.380 inches as supplied

## **Main Body Large End Inside Diameter:**

0.940 inches after unrestricted recovery

#### Distance From Top Of Shoulder To Small End Of Main Body:

1.390 inches after unrestricted recovery

## **End Largest Diameter:**

1.180 inches after unrestricted recovery

## Min. Tensile Strength (psi):

1200 pounds per square inch

#### Lip Height:

0.120 inches after unrestricted recovery

#### Lip Width:

0.040 inches after unrestricted recovery

## **Special Features:**

Includes drain holes

## Flexibility:

Flexible

## Height:

0.740 inches after unrestricted recovery

## Color:

Black

#### Material:

Plastic, polyolefin, rt-1304, raychem corp

#### Material:

Plastic, polyolefin, rt-1304, raychem corp

## **Style Designator:**

Boot-90 degrees

## **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# NSN 5970-00-110-8430

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A22500