

View Online at <https://aerobasegroup.com/nsn/5970-00-177-1420>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Distance From Centerline Of Main Body To End Of First Branch:

1.500 inches after unrestricted recovery

Main Body Inside Diameter:

1.200 inches as supplied

First Branch Inside Diameter:

0.700 inches as supplied

Main Body Wall Thickness:

0.090 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Main Bodylength:

3.170 inches as supplied

Angle Between Main Body And First Branch Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

One end main body reduced to 0.700 in. Min as supplied, 0.350 in. Maximum after unrestricted recovery; small end main body wall thk reduced to 0.050 in. Maximum as supplied, 0.050 in. Nom after unrestricted recovery

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500