

View Online at <https://aerobasegroup.com/nsn/5970-00-177-1473>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Main Body Inside Diameter:**

3.600 inches as supplied

**First Branch Inside Diameter:**

1.800 inches as supplied

**Second Branch Inside Diameter:**

1.800 inches as supplied

**Third Branch Inside Diameter:**

1.080 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

8.310 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.280 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.180 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.180 inches after unrestricted recovery

**Third Branch Wall Thickness:**

0.180 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

7.060 inches after unrestricted recovery

**Main Bodylength:**

15.370 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

30.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Flexibility:**

Semirigid

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-301, raychem corp

**Material:**

Plastic, polyolefin, rt-301, raychem corp

**Style Designator:**

Transition-1 to 3 cables

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500