NSN 5970-00-181-0610

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-181-0610

Reliability Indicator:

Not established

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.120 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.160 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.760 inches after unrestricted recovery

Main Bodylength:

5.910 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

One end of main body 1.060 in. Min id assupplied, 0.530 in. Maximum id after unrestricted recovery

Flexibility:

Flexible

Color:

Black

Material:

Rubber, neoprene, rt-501, @raychem corp

Material:

Rubber, neoprene, rt-501, @raychem corp

Style Designator:

Transition-45 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5970-00-181-0610

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500