Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-221-5303

## Wall Thickness:

Between 0.037 inches and 0.043 inches

## **Reliability Indicator:**

Not established

## **Inside Diameter:**

Between 0.565 inches and 0.590 inches

#### **Tempurature Rating:**

-30.0 degrees celsius and 75.0 degrees celsius

#### **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

#### Min. Tensile Strength (psi):

1800 pounds per square inch

## Flexibility:

Flexible

#### Color:

Natural

#### Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ub, grade a, class 1

## Material:

Plastic polyvinyl chloride

## Style Designator:

Nonshrinkable

## **Dielectric Material Voltage Rating Per Unit Thickness:**

480.0 volts per military /0.001 inch/

## **Specification Or Standard:**

1 category and 1 class and u form and a grade and 0.570 in. Size and ub subform and f type

## **Departure From Cited Designator:**

As mod by color

Shelf Life:

N/a

#### Unit Of Measure:

```
--
```

# Demilitarization:

No

Fiig:

## A22500

Mil-std (military Standard):

Mil-i-631 spec.