

View Online at <https://aerobasegroup.com/nsn/5970-00-246-3193>

**Wall Thickness:**

0.125 inches

**Reliability Indicator:**

Not established

**Inside Diameter:**

Between 0.245 inches and 0.260 inches

**Temperature Rating:**

-46.0 degrees celsius and 70.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant and oil resistant and cold resistant and crack resistant

**Min. Tensile Strength (psi):**

1450 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Clear

**Material:**

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ub, grade b, class 1

**Material:**

Plastic polyvinyl chloride

**Style Designator:**

Nonshrinkable

**Dielectric Material Voltage Rating Per Unit Thickness:**

350.0 volts per military /0.001 inch/

**Specification Or Standard:**

1 category and 1 class and u form and b grade and 0.250 in. Size and ub subform and f type

**Departure From Cited Document:**

As mod by color

**Departure From Cited Designator:**

As mod by wall thk

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500

**Mil-std (military Standard):**

Mil-i-631 spec.