## NSN 5970-00-248-4010

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-248-4010 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Main Body Wall Thickness: 0.120 inches after unrestricted recovery Main Bodylength: 3.000 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.580 inches as supplied Main Body Large End Inside Diameter: 1.180 inches as supplied Distance From Bottom Of Shoulder To Large End Of Main Body: 1.660 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 0.620 inches after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Includes injection and vent ports; small end wall thk 0.070 in after recovery Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Boot-straight **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A22500