## NSN 5970-00-283-9968

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-283-9968
Reliability Indicator:
Not established
Environmental Protection:
Flame resistant and mildew resistant and solvent resistant and water resistant
Distance From Centerline Of Main Body To End Of First Branch:
Any acceptable as supplied
Main Body Inside Diameter:
0.270 inches after unrestricted recovery
First Branch Inside Diameter:
0.270 inches after unrestricted recovery
Main Body Wall Thickness:
0.060 inches as supplied
First Branch Wall Thickness:
0.060 inches after unrestricted recovery
Main Bodylength:
Any acceptable as supplied
Angle Between Main Body And First Branch Centerlines In Deg:
90.0 after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Includes mounting ports
Flexibility:
Flexible
Color:
Black
Material:
Rubber, neoprene, rt-501, rayclad tubes inc
Material:
Rubber, neoprene, rt-501, rayclad tubes inc
Style Designator:
Transition-t
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A22500