Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-357-7472

Reliability Indicator:	
Not established	
Tempurature Rating:	
-55.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant	
Main Body Inside Diameter:	
1.200 inches as supplied	
First Branch Inside Diameter:	
0.800 inches as supplied	
Distance From Intersecting Centerline Of Main Body To End Of First Branch:	
2.000 inches after unrestricted recovery	
Main Body Wall Thickness:	
0.100 inches after unrestricted recovery	
First Branch Wall Thickness:	
0.070 inches after unrestricted recovery	
Distance From Edge Of Main Body To Intersecting Centerlines:	
1.250 inches after unrestricted recovery	
Main Bodylength:	
3.250 inches after unrestricted recovery	
Angle Between Main Body And First Branch Centerlines In Deg:	
30.0 after unrestricted recovery	
Min. Tensile Strength (psi):	
1200 pounds per square inch	
Flexibility:	
Flexible	
Color:	
Black	
Material:	
Plastic, polyolefin, rt-1304, raychem corp	
Material:	
Plastic, polyolefin, rt-1304, raychem corp	
Style Designator:	
Transition-45 degrees	
Dielectric Material Voltage Rating Per Unit Thickness:	
225.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5970-00-357-7472

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

