Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-409-8431

New Online at https://defobdsegfoup.com/nsi#5576-00-403-0451
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Large End Wall Thickness Of Main Body:
0.070 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.070 inches after unrestricted recovery
Distance From Intersecting Centerlines To Edge Of Small End:
1.720 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
0.900 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.420 inches as supplied
Main Body Large End Inside Diameter:
1.420 inches as supplied
Distance From Top Of Shoulder To Small End Of Main Body:
0.500 inches after unrestricted recovery
Angle Between Large End And Small End Centerlines In Deg:
90.0 after unrestricted recovery
Min. Tensile Strength (psi):
15 pounds per square inch
Special Features:
Includes drain holes
Flexibility:
Flexible
Height:
1.380 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A22500