

View Online at <https://aerobasegroup.com/nsn/5970-00-464-5892>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.000 inches as supplied

First Branch Inside Diameter:

0.500 inches as supplied

Second Branch Inside Diameter:

0.500 inches as supplied

Third Branch Inside Diameter:

0.500 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

Any acceptable as supplied

Main Body Wall Thickness:

0.060 inches as supplied

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Third Branch Wall Thickness:

0.060 inches as supplied

Distance From Edge Of Main Body To Intersecting Centerlines:

Any acceptable as supplied

Main Bodylength:

4.250 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

Any acceptable as supplied

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Unpackaged Unit Weight:

0.037 pounds

Style Designator:

Transition-1 to 3 cables

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500