Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-488-6623

| Wall Thickness:  |      |
|--|------|
| Any acceptable   |      |
| Reliability Indicator:                                   |      |
| Not established  |      |
| Inside Diameter:   |      |
| Between 0.325 inches and 0.347 inches                    |      |
| Overall Length:  |      |
| Any acceptable   |      |
| Tempurature Rating:                                      |      |
| 155.0 degrees celsius                                    |      |
| Coating Material:  |      |
| Plastic, acrylic   |      |
| Environmental Protection:                                |      |
| Flame resistant  |      |
| Flexibility:   |      |
| Flexible   |      |
| Color:   |      |
| Natural  |      |
| Material:  |      |
| Fiberglass, nema vs 1-1962, type 6, grade a              |      |
| Material:  |      |
| Glass fiber  |      |
| Style Designator:  |      |
| Nonshrinkable  |      |
| Specification Data:                                      |      |
| 81705-vs1-1962 professional/industrial association stand | Jard |
| Shelf Life:  |      |
| N/a  |      |
| Unit Of Measure:   |      |
|  |      |
| Demilitarization:  |      |
| No   |      |
| Fiig:  |      |
| A22500   |      |