

View Online at https://aerobasegroup.com/nsn/5970-00-522-1664

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 150.0 degrees celsius
Environmental Protection:
Flame resistant
Large End Wall Thickness Of Main Body:
0.040 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.040 inches after unrestricted recovery
Distance From Intersecting Centerlines To Edge Of Small End:
0.680 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
0.610 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.650 inches as supplied
Main Body Large End Inside Diameter:
0.650 inches as supplied
Distance From Top Of Shoulder To Small End Of Main Body:
0.190 inches after unrestricted recovery
Angle Between Large End And Small End Centerlines In Deg:
90.0 after unrestricted recovery
Special Features:
Adhesive ends
Flexibility:
Semirigid
Height:
0.790 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyolefin
Material:
Plastic polyolefin
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

--

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500