Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-543-1471

### Wall Thickness:

Between 0.022 inches and 0.028 inches

# **Reliability Indicator:**

Not established

## Inside Diameter:

Between 0.438 inches and 0.462 inches

### **Overall Length:**

Any acceptable

### **Tempurature Rating:**

-10.0 degrees celsius and 105.0 degrees celsius

### **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

### Min. Tensile Strength (psi):

1800 pounds per square inch

### Flexibility:

Flexible

Color:

Black

## Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ua, grade c, class 1, category 1

## Material:

Plastic polyvinyl chloride

Style Designator:

Nonshrinkable

### **Dielectric Material Voltage Rating Per Unit Thickness:**

630.0 volts per military /0.001 inch/

### **Specification Or Standard:**

1 category and i class and u form and c grade and 7/16 in. Size and ua subform and f type

### **Departure From Cited Document:**

As mod by color

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A22500

## Mil-std (military Standard):

Mil-i-631 spec.