Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-552-0250

| ····· ································    |  |
|---|--|
| Wall Thickness:                           |  |
| 0.045 inches                              |  |
| Dielectric Withstanding Voltage In Volts: |  |
| 2500.0                                    |  |
| Reliability Indicator:                    |  |
| Not established                           |  |
| Inside Diameter:                          |  |
| Between 0.204 inches and 0.224 inches     |  |
| Overall Length:                           |  |
| Between 2.500 feet and 3.500 feet         |  |
| Tempurature Rating:                       |  |
| 200.0 degrees celsius                     |  |
| Coating Material:                         |  |
| Varnished                                 |  |
| Environmental Protection:                 |  |
| Any acceptable                            |  |
| Impregnation Material:                    |  |
| Silicone                                  |  |
| Flexibility:                              |  |
| Flexible                                  |  |
| Color:                                    |  |
| Brown                                     |  |
| Material:                                 |  |
| Glass braid, mil-i-3190, class h-c-1      |  |
| Style Designator:                         |  |
| Nonshrinkable                             |  |
| Specification Or Standard:                |  |
| H-c-1 class and 4awg size                 |  |
| Shelf Life:                               |  |
| N/a                                       |  |
| Unit Of Measure:                          |  |
|   |  |
| Demilitarization:                         |  |
| No  |  |
| Filg:                                     |  |
| A22500                                    |  |
| Mil-std (military Standard):              |  |
| Mil-i-3190 spec.                          |  |
|   |  |