Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-574-8581

Reliability Indicator:	
Not established	
Tempurature Rating:	
-55.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant	
Large End Wall Thickness Of Main Body:	
0.060 inches after unrestricted recovery	
Small End Wall Thickness Of Main Body:	
0.060 inches after unrestricted recovery	
Distance From Intersecting Centerlines To Edge Of Small End:	
2.620 inches after unrestricted recovery	
Main Body Small End Inside Diameter:	
1.000 inches as supplied	
Distance From Top Of Shoulder To Small End Of Main Body:	
0.420 inches after unrestricted recovery	
Angle Between Large End And Small End Centerlines In Deg:	
40.0 and 50.0 after unrestricted recovery	
Min. Tensile Strength (psi):	
1500 pounds per square inch	
Special Features:	
Large end has lip	
Flexibility:	
Semirigid	
Height:	
2.620 inches after unrestricted recovery	
Color:	
Black	
Material:	
Plastic, polyolefin, rt-301, raychem corp	
Material:	
Plastic, polyolefin, rt-301, raychem corp	
Dielectric Material Voltage Rating Per Unit Thickness:	
200.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A22500	