Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-596-2143

	Withstanding Voltage In Volts:
200.0	
Reliability	Indicator:
Not establi	shed
Tempuratu	ure Rating:
-55.0 degre	ees celsius and 225.0 degrees celsius
Environme	ental Protection:
Flame resis	stant and mildew resistant and petroleum resistant and hydraulic fluid
Main Body	v Wall Thickness:
0.130 inche	es after unrestricted recovery
Main Body	/length:
5.120 inche	es after unrestricted recovery
Main Body	v Small End Inside Diameter:
2.040 inche	es as supplied
Main Body	/ Large End Inside Diameter:
2.040 inche	es as supplied
Distance F	rom Bottom Of Shoulder To Large End Of Main Body:
2.830 inche	es after unrestricted recovery
Distance F	rom Top Of Shoulder To Small End Of Main Body:
1.500 inche	es after unrestricted recovery
Min. Tensi	le Strength (psi):
1200 poun	ds per square inch
Flexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, po	lyolefin, rt-301, raychem corp
Material:	
Plastic, po	lyolefin, rt-301, raychem corp
Style Desi	gnator:
Boot-straig	ht
Shelf Life:	
N/a	
Unit Of Me	easure:
Demilitariz	zation:
No	
Fiig:	
A22500	