Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-615-5538

#### Wall Thickness:

Between 0.030 inches and 0.040 inches

# **Reliability Indicator:**

Not established

# **Inside Diameter:**

Between 1.000 inches and 1.036 inches

# **Overall Length:**

Any acceptable

#### **Tempurature Rating:**

-30.0 degrees celsius and 75.0 degrees celsius

# **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

# Min. Tensile Strength (psi):

1800 pounds per square inch

#### Flexibility:

Flexible

#### Color:

White

# Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, grade a, class 1, category 1

# Style Designator:

Nonshrinkable

# Dielectric Material Voltage Rating Per Unit Thickness:

525.0 volts per military /0.001 inch/

# **Specification Or Standard:**

1 category and i class and u form and a grade and 1 in. Size and ua subform and a type

# **Departure From Cited Document:**

As mod by color

Shelf Life:

N/a

# Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A22500

Mil-std (military Standard):

Mil-i-631 spec.