Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-617-5798

#### Wall Thickness:

Between 0.022 inches and 0.028 inches

## **Reliability Indicator:**

Not established

### Inside Diameter:

Between 0.375 inches and 0.399 inches

#### **Overall Length:**

Any acceptable

#### **Tempurature Rating:**

-30.0 degrees celsius and 75.0 degrees celsius

#### **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

#### Min. Tensile Strength (psi):

1800 pounds per square inch

#### Flexibility:

Flexible

#### Color:

Clear

### Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, grade a, class 1, category 1

# Style Designator:

Nonshrinkable

### Dielectric Material Voltage Rating Per Unit Thickness:

630.0 volts per military /0.001 inch/

### **Specification Or Standard:**

1 category and i class and u form and a grade and 3/8 in. Size and ua subform and f type

#### **Departure From Cited Document:**

As mod by color

Shelf Life:

N/a

#### Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A22500

Mil-std (military Standard):

Mil-i-631 spec.