## NSN 5970-00-753-0824

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-753-0824 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Large End Wall Thickness Of Main Body: 0.050 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.040 inches after unrestricted recovery Distance From Intersecting Centerlines To Edge Of Small End: 0.800 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 0.630 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.180 inches as supplied Main Body Large End Inside Diameter: 0.420 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 0.200 inches after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Semirigid Height: 0.800 inches after unrestricted recovery Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5970-00-753-0824

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500