Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-755-4424

#### Wall Thickness:

Between 0.017 inches and 0.023 inches

# **Reliability Indicator:**

Not established

### **Inside Diameter:**

Between 0.325 inches and 0.347 inches

### **Overall Length:**

Any acceptable

#### **Tempurature Rating:**

-30.0 degrees celsius and 75.0 degrees celsius

### **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

### Min. Tensile Strength (psi):

1800 pounds per square inch

#### Flexibility:

Flexible

Color:

White

### Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, grade a, class 1, category 1

# Style Designator:

Nonshrinkable

# Dielectric Material Voltage Rating Per Unit Thickness:

700.0 volts per military /0.001 inch/

# **Specification Or Standard:**

1 category and i class and u form and a grade and 0awg size and ua subform and f type

### **Departure From Cited Document:**

As mod by color

Shelf Life:

N/a

### Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

### A22500

Mil-std (military Standard):

Mil-i-631 spec.