Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-764-9094

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Distance From Intersecting Centerlines To Edge Of Small End:
2.490 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
0.690 inches after unrestricted recovery
Main Body Wall Thickness:
0.120 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.750 inches as supplied
Main Body Large End Inside Diameter:
2.280 inches as supplied
Min. Tensile Strength (psi):
1500 pounds per square inch
Special Features:
Small end has wall thickness of 0.040 in; large end has lip
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Style Designator:
Boot-rectangular-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500