Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-818-7385

#### Wall Thickness:

Between 0.030 inches and 0.040 inches

# **Reliability Indicator:**

Not established

# **Inside Diameter:**

Between 0.750 inches and 0.786 inches

# **Overall Length:**

Any acceptable

## **Tempurature Rating:**

-10.0 degrees celsius and 105.0 degrees celsius

# **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant and heat resistant

#### Min. Tensile Strength (psi):

1800 pounds per square inch

#### Flexibility:

Flexible

#### Color:

Blue

## Material:

Plastic, mil-i-631, type f, form u, grade c, class 1, category 1

# Style Designator:

Nonshrinkable

# **Dielectric Material Voltage Rating Per Unit Thickness:**

525.0 volts per military /0.001 inch/

# **Specification Or Standard:**

1 category and i class and u form and c grade and 3/4 in. Size and ua subform and f type

# **Departure From Cited Document:**

As mod by color

Shelf Life:

N/a

#### Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

# A22500

Mil-std (military Standard):

Mil-i-631 spec.