Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-827-6567

| Reliability Indicator:                                       |
|--|
| Not established  |
| Overall Length:  |
| Any acceptable   |
| Tempurature Rating:  |
| -55.0 degrees celsius and 110.0 degrees celsius              |
| Environmental Protection:                                    |
| Corrosion resistant and mildew resistant and water resistant |
|  |
| Expanded Inside Diameter:<br>0.750 inches                    |
| Recovered Inside Diameter:                                   |
|  |
| 0.313 inches   |
| Recovered Wall Thickness:                                    |
| 0.065 inches   |
| Heat Shrinkage Rating In Percent:                            |
| 58.3   |
| Min. Tensile Strength (psi):                                 |
| 1500 pounds per square inch                                  |
| Special Features:  |
| Meltable inner wall  |
| Flexibility:   |
| Semirigid  |
| Color:   |
| Yellow   |
| Material:  |
| Plastic, polyolefin, mil-i-23053/4, class 1                  |
| Material:  |
| Plastic polyolefin   |
| Style Designator:  |
| Shrinkable   |
| Dielectric Material Voltage Rating Per Unit Thickness:       |
| 500.0 volts per military /0.001 inch/                        |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A22500   |
|  |