NSN 5970-00-837-2164

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5970-00-837-2164 |
|---|
| Dielectric Withstanding Voltage In Volts: |
| 200.0 |
| Reliability Indicator: |
| Not established |
| Tempurature Rating: |
| -55.0 degrees celsius and 225.0 degrees celsius |
| Environmental Protection: |
| Any acceptable |
| Large End Wall Thickness Of Main Body: |
| 0.150 inches after unrestricted recovery |
| Small End Wall Thickness Of Main Body: |
| 0.150 inches after unrestricted recovery |
| Distance From Intersecting Centerlines To Edge Of Small End: |
| 3.840 inches after unrestricted recovery |
| Distance From Centerline Of Small End To Edge Of Large End: |
| 1.640 inches after unrestricted recovery |
| Main Body Small End Inside Diameter: |
| 2.600 inches as supplied |
| Main Body Large End Inside Diameter: |
| 2.600 inches as supplied |
| Distance From Top Of Shoulder To Small End Of Main Body: |
| 1.600 inches after unrestricted recovery |
| Angle Between Large End And Small End Centerlines In Deg: |
| 90.0 after unrestricted recovery |
| Heat Shrinkage Rating In Percent: |
| 250.0 |
| Min. Tensile Strength (psi): |
| 1500 pounds per square inch |
| Flexibility: |
| Semirigid |
| Height: |
| 2.600 inches after unrestricted recovery |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin |
| Material: |
| Plastic polyolefin |
| Style Designator: |
| Boot-90 degrees |

Shelf Life: N/a

NSN 5970-00-837-2164

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A22500