NSN 5970-00-879-7314

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-879-7314 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant and solvent resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 4.850 inches after unrestricted recovery Main Body Inside Diameter: 2.190 inches as supplied **First Branch Inside Diameter:** 2.190 inches as supplied Main Body Wall Thickness: 0.130 inches after unrestricted recovery **First Branch Wall Thickness:** 0.130 inches after unrestricted recovery Main Bodylength: 9.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-501, raychem corp Material: Rubber, neoprene, rt-501, raychem corp **Style Designator:** Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A22500