Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-892-0936

### Wall Thickness:

Between 0.017 inches and 0.023 inches

## **Reliability Indicator:**

Not established

## **Inside Diameter:**

Between 0.204 inches and 0.224 inches

### **Overall Length:**

Any acceptable

### **Tempurature Rating:**

-10.0 degrees celsius and 105.0 degrees celsius

## **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant and heat resistant

### Min. Tensile Strength (psi):

1800 pounds per square inch

### Flexibility:

Flexible

#### Color:

Yellow

### Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ua, grade c, class 1, category 1

## Material:

Plastic polyvinyl chloride

## Style Designator:

Nonshrinkable

## **Dielectric Material Voltage Rating Per Unit Thickness:**

700.0 volts per military /0.001 inch/

## **Specification Or Standard:**

1 category and i class and u form and c grade and 4awg size and ua subform and f type

## **Departure From Cited Designator:**

As modified by color

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A22500

## Mil-std (military Standard):

Mil-i-631 spec.