Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-899-6666

#### Wall Thickness:

Between 0.017 inches and 0.023 inches

# **Reliability Indicator:**

Not established

#### **Inside Diameter:**

Between 0.325 inches and 0.347 inches

## **Overall Length:**

Any acceptable

#### **Tempurature Rating:**

-46.0 degrees celsius and 70.0 degrees celsius

### **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant and cold resistant and crack resistant

#### Min. Tensile Strength (psi):

1450 pounds per square inch

#### Flexibility:

Flexible

### Color:

Clear

## Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ua, grade b, class 1

## Style Designator:

Nonshrinkable

## Dielectric Material Voltage Rating Per Unit Thickness:

650.0 volts per military /0.001 inch/

## **Specification Or Standard:**

1 category and 1 class and u form and b grade and 0 awg size and ua subform and f type

### **Departure From Cited Document:**

As mod by color

Shelf Life:

N/a

### Unit Of Measure:

```
---
```

## Demilitarization:

No

Fiig:

A22500

Mil-std (military Standard):

Mil-i-631 spec.