## NSN 5970-00-908-5001

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-908-5001 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Main Body Inside Diameter: 1.200 inches as supplied **First Branch Inside Diameter:** 0.800 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 2.000 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery **First Branch Wall Thickness:** 0.070 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 1.250 inches after unrestricted recovery Main Bodylength: 3.250 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 30.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Transition-45 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5970-00-908-5001

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500