Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-908-5162

	/aerobasegroup.com/nsn/5970-00-908-5162
Dielectric Withstand	ing Voltage In Volts:
200.0	
Reliability Indicator:	
Not established	
Tempurature Rating	:
-55.0 degrees celsius	and 225.0 degrees celsius
Environmental Prote	ection:
Any acceptable	
Main Body Inside Di	ameter:
0.520 inches as supp	lied
First Branch Inside I	Diameter:
0.260 inches as supp	lied
Distance From Inters	secting Centerline Of Main Body To End Of First Branch:
0.840 inches after un	restricted recovery
Main Body Wall Thic	kness:
0.060 inches as supp	lied
First Branch Wall Th	ickness:
0.040 inches as supp	lied
Distance From Edge	Of Main Body To Intersecting Centerlines:
0.900 inches after un	restricted recovery
Main Bodylength:	
1.740 inches as supp	lied
Angle Between Main	Body And First Branch Centerlines In Deg:
45.0 after unrestricted	d recovery
Min. Tensile Strengt	h (psi):
1500 pounds per squa	are inch
Flexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, polyolefin	
Material:	
Plastic polyolefin	
Style Designator:	
Transition-45 degrees	i de la constante d
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 5970-00-908-5162

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

**Fiig:** A22500

