

View Online at https://aerobasegroup.com/nsn/5970-00-908-8387

| view Online at https://aerobasegroup.com/nsi//3570-00-300-0307 |
|--|
| Dielectric Withstanding Voltage In Volts: |
| 200.0 |
| Reliability Indicator: |
| Not established |
| Tempurature Rating: |
| -55.0 degrees celsius and 225.0 degrees celsius |
| Environmental Protection: |
| Any acceptable |
| Main Body Inside Diameter: |
| 0.520 inches as supplied |
| First Branch Inside Diameter: |
| 0.260 inches as supplied |
| Distance From Intersecting Centerline Of Main Body To End Of First Branch: |
| 0.920 inches after unrestricted recovery |
| Main Body Wall Thickness: |
| 0.060 inches as supplied |
| First Branch Wall Thickness: |
| 0.040 inches as supplied |
| Distance From Edge Of Main Body To Intersecting Centerlines: |
| 0.900 inches after unrestricted recovery |
| Main Bodylength: |
| 1.940 inches after unrestricted recovery |
| Angle Between Main Body And First Branch Centerlines In Deg: |
| 45.0 after unrestricted recovery |
| Min. Tensile Strength (psi): |
| 1500 pounds per square inch |
| Flexibility: |
| Semirigid |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin |
| Material: |
| Plastic polyolefin |
| Style Designator: |
| Transition-45 degrees |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5970-00-908-8387

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

