Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-917-7155

| Dielectric Withstanding Voltage In Volts: | |
|---|----|
| 200.0 | |
| Reliability Indicator: | |
| Not established | |
| Tempurature Rating: | |
| -55.0 degrees celsius | |
| Environmental Protection: | |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistar | nt |
| Distance From Centerline Of Main Body To End Of First Branch: | |
| 2.360 inches after unrestricted recovery | |
| Main Body Inside Diameter: | |
| 1.060 inches as supplied | |
| First Branch Inside Diameter: | |
| 1.060 inches as supplied | |
| Main Body Wall Thickness: | |
| 0.100 inches after unrestricted recovery | |
| First Branch Wall Thickness: | |
| 0.100 inches after unrestricted recovery | |
| Main Bodylength: | |
| 4.730 inches after unrestricted recovery | |
| Angle Between Main Body And First Branch Centerlines In Deg: | |
| 90.0 after unrestricted recovery | |
| Min. Tensile Strength (psi): | |
| 1500 pounds per square inch | |
| Flexibility: | |
| Semirigid | |
| Color: | |
| Black | |
| Material: | |
| Plastic, polyolefin, rt-301, raychem corp | |
| Material: | |
| Plastic, polyolefin, rt-301, raychem corp | |
| Style Designator: | |
| Transition-t | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A22500 | |