

View Online at <https://aerobasegroup.com/nsn/5970-00-923-0755>

Dielectric Withstanding Voltage In Volts:

200.0

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 225.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Large End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

2.110 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

1.140 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.840 inches as supplied

Main Body Large End Inside Diameter:

1.490 inches as supplied

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Height:

1.730 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, high voltage engineering corp

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, high voltage engineering corp

Style Designator:

Boot-90 degrees

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500