Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-923-7173

New Online at https://defobasegroup.com/nsil/0370-00-323-7773
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Distance From Centerline Of Main Body To End Of First Branch:
1.160 inches after unrestricted recovery
Main Body Inside Diameter:
0.520 inches as supplied
First Branch Inside Diameter:
0.520 inches as supplied
Main Body Wall Thickness:
0.060 inches as supplied
First Branch Wall Thickness:
0.060 inches after unrestricted recovery
Main Bodylength:
2.310 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
90.0 after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Style Designator:
Transition-t
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500