

View Online at <https://aerobasegroup.com/nsn/5970-00-936-8576>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

135.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant and solvent resistant and water resistant

**Main Body Inside Diameter:**

1.060 inches as supplied 0.490 inches after unrestricted recovery

**First Branch Inside Diameter:**

0.520 inches as supplied 0.240 inches after unrestricted recovery

**Second Branch Inside Diameter:**

0.520 inches as supplied 0.240 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

1.700 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.100 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

1.500 inches after unrestricted recovery

**Angle Between Main Body And Second Branch Centerlines In Deg:**

22.5 after unrestricted recovery

**Min. Tensile Strength (psi):**

600 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Rubber, silicone, rt-602, rayclad tubes inc

**Material:**

Rubber, silicone, rt-602, rayclad tubes inc

**Style Designator:**

Transition-y

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500