

View Online at <https://aerobasegroup.com/nsn/5970-00-936-8580>

**Dielectric Withstanding Voltage In Volts:**

200.0

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius and 150.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant and solvent resistant and water resistant

**Large End Wall Thickness Of Main Body:**

0.140 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.050 inches after unrestricted recovery

**Distance From Intersecting Centerlines To Edge Of Small End:**

1.890 inches after unrestricted recovery

**Distance From Centerline Of Small End To Edge Of Large End:**

0.970 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

0.580 inches as supplied

**Main Body Large End Inside Diameter:**

1.180 inches as supplied

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.490 inches after unrestricted recovery

**Angle Between Large End And Small End Centerlines In Deg:**

90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

With port holes

**Flexibility:**

Flexible

**Height:**

1.520 inches after unrestricted recovery

**Color:**

Black

**Material:**

Rubber, neoprene, rt-501, raychem corp

**Material:**

Rubber, neoprene, rt-501, raychem corp

**Style Designator:**

Boot-90 degrees

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500