NSN 5970-00-939-6955

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-939-6955

T	m	nı	ırat	ure	Ra	tin	u.
15	71 I I	υu	ıιαι	uie	I\a		u.

-67.0 degrees celsius and 175.0 degrees celsius

Environmental Protection:

Chemical resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.005 inches as supplied and 0.011 inches as supplied

Main Bodylength:

0.300 inches as supplied and 0.360 inches as supplied

Main Body Small End Inside Diameter:

0.190 inches after unrestricted recovery

Main Body Large End Inside Diameter:

0.400 inches as supplied and 0.450 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

Any acceptable after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

Any acceptable after unrestricted recovery

Min. Tensile Strength (psi):

5000 pounds per square inch

Flexibility:

Semirigid

Color:

Natural

Material:

Plastic, polyvinylidene fluoride

Material:

Plastic polyvinylidene fluoride

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

500.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500