Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-939-8489

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 1.520 inches after unrestricted recovery Main Body Inside Diameter: 1.060 inches as supplied **First Branch Inside Diameter:** 0.520 inches as supplied Main Body Wall Thickness: 0.100 inches after unrestricted recovery **First Branch Wall Thickness:** 0.060 inches after unrestricted recovery Main Bodylength: 4.240 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500