Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-940-8274

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thickness:
0.122 inches after unrestricted recovery
Main Bodylength:
5.130 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.400 inches as supplied
Main Body Large End Inside Diameter:
1.850 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
3.020 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
2.000 inches after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500