NSN 5970-00-954-6896

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-954-6896

Dielectric Withstanding Voltage In Volts:
200.0
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Any acceptable
Main Body Inside Diameter:
2.190 inches as supplied
First Branch Inside Diameter:
0.520 inches as supplied
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
2.830 inches after unrestricted recovery
Main Body Wall Thickness:
0.180 inches after unrestricted recovery
First Branch Wall Thickness:
0.060 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
3.280 inches after unrestricted recovery
Main Bodylength:
7.280 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
45.0 after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin
Material:
Plastic polyolefin
Style Designator:
Transition-45 degrees
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5970-00-954-6896

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500