## NSN 5970-00-956-5047

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-956-5047

**Reliability Indicator:** 

Not established

**Tempurature Rating:** 

-55.0 degrees celsius

**Environmental Protection:** 

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Large End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

2.110 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

1.150 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.730 inches as supplied

Main Body Large End Inside Diameter:

1.730 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

0.680 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 as supplied

Markings:

Not known

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Height:

1.730 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

**Style Designator:** 

Boot-90 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:** 

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

## NSN 5970-00-956-5047

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A22500