

View Online at <https://aerobasegroup.com/nsn/5970-00-956-9392>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Flame resistant and solvent resistant and mildew resistant and water resistant

Main Body Inside Diameter:

0.680 inches as supplied

First Branch Inside Diameter:

0.440 inches as supplied

Second Branch Inside Diameter:

0.440 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.500 inches after unrestricted recovery

Main Body Wall Thickness:

0.090 inches after unrestricted recovery

First Branch Wall Thickness:

0.090 inches after unrestricted recovery

Second Branch Wall Thickness:

0.090 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

3.250 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Rubber, neoprene, rt-501, raychem corp

Material:

Rubber, neoprene, rt-501, raychem corp

Style Designator:

Transition-y

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500