

View Online at <https://aerobasegroup.com/nsn/5970-00-968-0565>

Dielectric Withstanding Voltage In Volts:

10000.0

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 80.0 degrees celsius

Environmental Protection:

Any acceptable

Main Body Inside Diameter:

1.060 inches as supplied

First Branch Inside Diameter:

0.520 inches as supplied

Second Branch Inside Diameter:

0.520 inches as supplied

Third Branch Inside Diameter:

0.520 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.980 inches as supplied

Main Body Wall Thickness:

0.120 inches after unrestricted recovery

First Branch Wall Thickness:

0.070 inches after unrestricted recovery

Second Branch Wall Thickness:

0.070 inches after unrestricted recovery

Third Branch Wall Thickness:

0.060 inches as supplied

Distance From Edge Of Main Body To Intersecting Centerlines:

1.690 inches as supplied

Main Bodylength:

4.040 inches as supplied

Angle Between Main Body And First Branch Centerlines In Deg:

35.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Rubber, chloroprene

Material:

Rubber chloroprene class cr

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500