

View Online at <https://aerobasegroup.com/nsn/5970-00-968-0574>

Dielectric Withstanding Voltage In Volts:

10000.0

Tempurature Rating:

-55.0 degrees celsius and 80.0 degrees celsius

Environmental Protection:

Any acceptable

Main Body Inside Diameter:

2.190 inches as supplied

First Branch Inside Diameter:

1.050 inches as supplied

Second Branch Inside Diameter:

1.060 inches as supplied

Third Branch Inside Diameter:

1.060 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.650 inches after unrestricted recovery

Main Body Wall Thickness:

0.220 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches as supplied

Second Branch Wall Thickness:

0.120 inches after unrestricted recovery

Third Branch Wall Thickness:

0.100 inches as supplied

Distance From Edge Of Main Body To Intersecting Centerlines:

3.850 inches after unrestricted recovery

Main Bodylength:

8.330 inches as supplied

Angle Between Main Body And First Branch Centerlines In Deg:

35.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Rubber, chloroprene

Material:

Rubber chloroprene class cr

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500