## NSN 5970-00-971-6383



Special Purpose Electrical Insulation Sleeving - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5970-00-971-6383 **Dielectric Withstanding Voltage In Volts:** 200.0 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius and 225.0 degrees celsius **Environmental Protection:** Any acceptable Main Body Inside Diameter: 1.060 inches as supplied **First Branch Inside Diameter:** 0.520 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Semirigid Color: Black Material: Plastic, polyolefin

Material: Plastic polyolefin **Style Designator:** Transition-45 degrees Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5970-00-971-6383

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500