## NSN 5970-00-971-7107

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-971-7107 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 2.230 inches after unrestricted recovery Main Body Inside Diameter: 1.160 inches as supplied **First Branch Inside Diameter:** 1.160 inches as supplied Main Body Wall Thickness: 0.100 inches after unrestricted recovery **First Branch Wall Thickness:** 0.100 inches after unrestricted recovery Main Bodylength: 3.670 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** One end main body reduced to 0.380 in. Min id as supplied, 0.210 in. Maximum id after unrestricted recovery, and 0.070 in. Nom wall thk after unrestricted recovery Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5970-00-971-7107

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500