Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-983-7895

| Reliability Indicator:                |  |
|---------------------------------------|--|
| Not established                       |  |
| Overall Length:                       |  |
| Any acceptable                        |  |
| Tempurature Rating:                   |  |
| -55.0 degrees celsius and 135.0 deg   |  |
| Environmental Protection:             | Jiees ceisius                                |
|                                       | ant and mildew resistant and water resistant |
| Expanded Inside Diameter:             |  |
| 0.375 inches                          |  |
| Recovered Inside Diameter:            |  |
| 0.187 inches                          |  |
| Recovered Wall Thickness:             |  |
| Between 0.022 inches and 0.028 inc    | shes   |
| Heat Shrinkage Rating In Percent:     |  |
| 50.0                                  |  |
| Min. Tensile Strength (psi):          |  |
| 1500 pounds per square inch           |  |
| Flexibility:                          |  |
| Flexible                              |  |
| Color:                                |  |
| Purple                                |  |
| Material:                             |  |
| Plastic, polyolefin, mil-i-23053/5, c | lass 1                                       |
| Material:                             |  |
| Plastic cross-linked polyolefin       |  |
| Style Designator:                     |  |
| Shrinkable                            |  |
| Dielectric Material Voltage Rating    | Per Unit Thickness:                          |
| 500.0 volts per military /0.001 inch/ |  |
| Shelf Life:                           |  |
| N/a                                   |  |
| Unit Of Measure:                      |  |
|                                       |  |
| Demilitarization:                     |  |
| No                                    |  |
| Fiig:                                 |  |
| A22500                                |  |